


Armourdoor Communal Entrance Doors AD40

Technical Specifications



www.hag.co.uk
Advice Line 0800 072 3444



Description

The Armourdoor Communal Entrance Doors AD40 is a high security door for entrances that experience high level use of pedestrian traffic. The steel door has double glazed units with two leaves each of 11.5mm anti-Bandit glass covered by 2mm stainless panels. Safety is incorporated into the door with anti-finger traps, concealed closers and frameless vision panels to minimise the threat of injury.

Common Use

Entrance door for offices, blocks of flats, housing association premises and retirement homes.

Dimensions

Single openings from 690mm to 1390mm. Double openings from 1290mm to 2600mm. All at heights up to 2900mm

Security Level

Medium / High Security



Product Overview

Operation

Manual

Finish

The Armourdoor AD40 communal entrance door is available powder coated from a standard range of colours. Wood grain, PVC laminate and Stainless steel are available.

Specification of Build

The AD40 door has a leaf thickness of 48mm made from 1.5mm corrosion resistant steel as standard. The door infill is constructed from a solid timber core for anti-vandal protection. Steel door frame is manufactured from 1.6mm thick steel zintec sheets. The communal door is supplied with a variable sub frame to allow up to 30mm tolerance for site installations. The frame is fitted with 1 dog bolt per hinge as standard. The Door is supplied with a standard driveable threshold.

Security

Concealed double mortice mounted deadlock

Optional Extras

Access Control system with the inclusion of concealed maglocks
Alternative Aperture shapes available.
Panels can be solid, glazed or louvered.

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.
