

# Seceuro Glide Garage Doors

Technical Specifications



[www.hag.co.uk](http://www.hag.co.uk)  
Advice Line 0800 072 3444

# Seceuro Glide Garage Doors



## What is it made from

Securo Glide Garage Door is a foam filled aluminium product.

## Typical Uses or Specific Use

Typical uses are a Domestic Garage Doors.

## Security Level

Medium to high Security.

## Benefit of product range

High insulation Value, quiet operation / smooth running with choice of standard colours.

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---

# Seceuro Glide Garage Doors



## Product Overview

### Description

Seceuro Glide, Seceuroglide is a double skin foam filled aluminium slat.

### Common use

Garage Doors

### Maximum Width

5400mm

### Dimensions

Nominally 77mm high x 19mm thick.

### Weight

6kg per square metre.

### Finish

White, brown, light beige, burgundy red, fir green or black & medium woodgrain (surcharges apply).

## Shutter Box Specification

### Construction

Roll formed aluminium in two sections; top and bottom boxes.

Bottom box removable for installation and maintenance and chamfered 45 degrees.

### Box sizes

Clear opening height (to underside of box):

2500mm box size 300mm

3500mm box side 350mm

### Finish

White, dark brown, Alternative standard RAL or BS colours at an extra cost.

## Guide Rail Specification

### Construction

Extruded aluminium with an integral box section for reinforcement and to facilitate fixing.

Neoprene seals for quiet and smooth operation.

### Dimensions

75mm wide x 34mm deep up to 4600mm wide

90mm wide x 34mm deep up to 5200mm wide

### Finish

White, brown, light beige, burgundy red, fir green or black.

### Acoustics

(Insulation 2.8 watts per m<sup>2</sup> Kelvin w/m<sup>2</sup>k

Decibel reduction at 500HZ = 18

Decibel reduction at 1000MHZ = 25k.

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---

# Seceuro Glide Garage Doors



## Operational Specification

### Single Phase Electric

Provision of a 13 amp fused spur is required for installation. A tubular motor within the barrel assembly with limit switches and the thermal cut out to prevent overheating. Draw 240 volts and 0.5 - 2.5 amps dependant upon the shutter size.

### Control

Seceurosmart Remote Control unit with 2 Hand transmitters, Wireless Safety edge, internal manual override and light

---

Product specification may change and it is advisable to consult with HAG technical advisors before specifying or ordering. HAG operates a policy of continuous improvement.

---

---

For further information about this product please call the HAG advice line on 0800 072 3444 or email [info@hag.co.uk](mailto:info@hag.co.uk)

---